





Paktron RA series cross reference guide

Overview

These series are stacked metallized polyester construction with a rated operating temperature range of -55°C to +125°C. Crosses are equivalent with regard to lead spacing and general electrical characteristics unless otherwise specified. Some dimensions of the capacitor body may vary, some electrical ratings of RA crosses exceed those of the competitive series.

Color Coding			
Current catalog offering	New Values	Producible values not currently in production	
			
Paktron PN	TDK Epcos PN	Wima PN	TDK B32520 ... B32529
63VDC 7.5mm LS			
334(1)063RA3	-	MKS4C033302C00(1)	-
474(1)063RA3	-	MKS4C034702C00(1)	B32520C0474(1)
684(1)063RA3	-	MKS4C036802E00(1)	B32520C0684(1)
105(1)063RA3	B32560J0105(1)	MKS4C041002E00(1)	B32520C0105(1)
155(1)063RA3	B32560J0155(1)	MKS4C041502F00(1)	B32520C0155(1)
225(1)100RA3	B32560J0225(1)	-	B32520C0225(1)
100VDC 7.5mm LS			
104(1)100RA3	-	MKS4D031002A00(1)	-
224(1)100RA3	B32560J1224(1)	MKS4D032202B00(1)	B32520C1224(1)
334(1)100RA3	B32560J1334(1)	MKS4D033302C00(1)	B32520C1334(1)

This guide serves as an application cross reference only. Mechanical and electrical characteristics should be compared using full specifications.

474(1)100RA3	B32560J1474(1)	MKS4D034702D00(1)	B32520C1474(1)
684(1)100RA3	B32560J1684(1)	MKS4D036802E00(1)	B32520C1684(1)
105(1)100RA3	B32560J1105(1)	MKS4D041002F00(1)	B32520C1105(1)
155(1)100RA3	B32560J1155(1)	-	-
225(1)100RA3	B32560J1225(1)	-	-
250VDC 7.5mm LS			
103(1)250RA3	-	MKS4F021002B00(1)	-
223(1)250RA3	-	MKS4F022202B00(1)	-
333(1)250RA3	-	MKS4F023302B00(1)	-
473(1)250RA3	B32560J3473(1)	MKS4F024702B00(1)	-
683(1)250RA3	B32560J3683(1)	MKS4F026802C00(1)	B32520C3683(1)
104(1)250RA3	B32560J3104(1)	MKS4F031002C00(1)	B32520C3104(1)
154(1)250RA3	B32560J3154(1)	MKS4F031502E00(1)	B32520C3154(1)
224(1)250RA3	B32560J3224(1)	MKS4F032202E00(1)	B32520C3224(1)
63VDC 10mm LS			
474(1)063RA4	-	MKS4C034703C00(1)	B32521C0474(1)
684(1)063RA4	-	MKS4C036803C00(1)	B32521C0684(1)
105(1)100RA4	B32561J0105(1)	MKS4C041003C00(1)	B32521C0105(1)
155(1)100RA4	B32561J0155(1)	MKS4C041503F00(1)	B32521C0155(1)
225(1)100RA4	B32561J0225(1)	MKS4C042203F00(1)	B32521C0225(1)
335(1)100RA4	B32561J0335(1)	MKS4C043303G00(1)	B32521C0335(1)
100VDC 10mm LS			
104(1)100RA4	-	MKS4D031003C00(1)	B32521C1104(1)
224(1)100RA4	-	MKS4D032203C00(1)	B32521C1224(1)
334(1)100RA4	-	MKS4D033303C00(1)	B32521C1334(1)
474(1)100RA4	-	MKS4D034703C00(1)	B32521C1474(1)
684(1)100RA4	B32561J1684(1)	MKS4D036803C00(1)	B32521C1684(1)
105(1)100RA4	B32561J1105(1)	MKS4D041003F00(1)	B32521C1105(1)
155(1)100RA4	B32561J1155(1)	MKS4D041503G00(1)	-
225(1)100RA4	B32561J1225(1)	-	-

This guide serves as an application cross reference only. Mechanical and electrical characteristics should be compared using full specifications.

335(1)100RA4	B32561J1335(1)	-	-
250VDC 10mm LS			
473(1)250RA4	-	MKS4F024703C00(1)	B32521C3473(1)
683(1)250RA4	-	MKS4F026803C00(1)	B32521C3683(1)
104(1)250RA4	B32561J3104(1)	MKS4F031003C00(1)	B32521C3104(1)
154(1)250RA4	B32561J3154(1)	MKS4F031503C00(1)	B32521C3154(1)
224(1)250RA4	B32561J3224(1)	MKS4F032203F00(1)	B32521C3224(1)
334(1)250RA4	B32561J3334(1)	MKS4F033303F00(1)	B32521C3334(1)
474(1)250RA4	B32561J3474(1)	MKS4F034703G00(1)	B32521C3474(1)
250VDC 15mm LS(1)			
224(1)250RA6	-	-	B32522C3224(1)
334(1)250RA6	-	-	B32522C3334(1)
474(1)250RA6	B32562J3474(1)	MKS4F034704C00(1)	B32522C3474(1)
684(1)250RA6	B32562J3684(1)	MKS4F036804D00(1)	B32522C3684(1)
105(1)250RA6	B32562J3105(1)	MKS4F041004F00(1)	B32522C3105(1)
400VDC 15mm LS			
104(1)400RA6	-	-	B32522E6104(1)
224(1)400RA6	B32562J6224(1)	MKS4G032204C00(1)	B32522E6224(1)
334(1)400RA6	B32562J6334(1)	MKS4G033304F00(1)	B32522E6334(1)
474(1)400RA6	B32562J6474(1)	MKS4G034704F00(1)	B32522E6474(1)

(1) Indicates tolerance for each series

J = ±5%

K = ±10%